

## Metglas® MBF-67 Nickel-Based Brazing Foil

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Metglas® MBF-67 Nickel-Based Brazing Foil

OTHER/GENERIC NAMES: MBF-67 Brazing Foil; MBF-67 Brazing Filler Metals

**PRODUCT USE:** Metal joining; Hard facing.

**MANUFACTURER:** Metglas®, Inc.

440 Allied Dr. Conway, SC - 29526

FOR MORE INFORMATION CALL:

IN CASE OF EMERGENCY CALL:

(Monday-Friday, 8:00am-5:00pm)

1-800-581-7654

(24 Hours/Day, 7 Days/Week) 1-800-581-7654 or Chemtrec 1-800-424-9300

### 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: A shiny metallic foil. As shipped, the primary hazard is the sharp edges of the product. Some individuals may develop allergic skin reactions after repeated handling. If melted in a fire, toxic fumes may be released.

### POTENTIAL HEALTH HAZARDS

**SKIN:** Handling of sharp edges may cause cuts. Repeated contact may cause allergic skin reaction

resulting in irritation or dermatitis.

**EYES:** Not a normal route of entry. Solid particles generated by grinding and sanding may cause

irritation.

**INHALATION:** Vapors and fumes resulting from the grinding, sanding, cutting and/or welding of this

material are harmful if inhaled. Symptoms may include irritation of throat and respiratory tract. Exposures may result in "metal fume fever" which can produce flu-like symptoms.

**INGESTION:** Not a route of entry.

**DELAYED EFFECTS:** Repeated inhalation of vapors and fumes may result in toxic effects to the lungs.

Cobalt and cobalt compounds and nickel and nickel compounds have caused cancer in laboratory animals and should be treated as 'possible' carcinogens. At present there is no reliable evidence that cobalt or nickel metal has caused cancer in humans.

Long term nickel exposure may affect kidney function.

Long term phosphorus exposures may cause kidney and liver effects.

Ingredients found on one of the OSHA designated carcinogen lists are listed below.



## Metglas® MBF-67 Nickel-Based Brazing Foil

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	<b>CAS NUMBER</b>	<b>WEIGHT</b> %
Boron	7440-42-8	0.1 - 2.0
Nickel	7440-02-0	60 - 80
Phosphorous	7723-14-0	5 - 12
Chromium	7440-47-3	20 - 30
Molybdenum	7439-98-7	0 - 5
Silicon	7440-21-3	0 - 3
Iron	7439-89-6	0 - 3

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of the MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

INGREDIENT NAME	NTP STATUS	<b>IARC STATUS</b>	<b>OSHA LIST</b>
Cobalt (possible trace impurity)	None	2b - possible	None
Nickel	Suspect carcinogen	carcinogen 2b - possible carcinogen	None
Health Rating (HMIS): Health: 2 Fire: 1	Reactivity: 0	Special:	None

### 4. FIRST AID MEASURES

**SKIN:** Wash hands with soap and water.

EYES: For irritation caused by particles of dust flush eyes with running water. Seek medical assistance if irritation

persists.

**INHALATION:** Remove to fresh air immediately. If breathing is difficult, get immediate medical assistance.

Oxygen may be given by a person trained and qualified to administer it.

**INGESTION:** Not a route of entry.

**ADVICE TO PHYSICIAN:** Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

### **FLAMMABLE PROPERTIES**

FLASH POINT: None

**FLASH POINT METHOD:** Not applicable

**AUTOIGNITION TEMPERATURE:** Not applicable

UPPER FLAME LIMIT (volume % in air):

LOWER FLAME LIMIT (volume % in air):

Not applicable
Not determined.

OSHA FLAMMABILITY CLASS: None



## Metglas® MBF-67 Nickel-Based Brazing Foil

### **EXTINGUISHING MEDIA:**

Use any standard agent for surrounding fire.

#### UNUSUAL FIRE AND EXPLOSION HAZARDS:

None

#### SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Toxic and irritating vapors may be released if the product melts or burns in a fire. Use self-contained respiratory protection.

### 6. ACCIDENTAL RELEASE MEASURES

#### IN CASE OF SPILL OR OTHER RELEASE:

Material is shipped as an article. Pick up and place into proper storage. Use caution in handling as edges are very sharp.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

### 7. HANDLING AND STORAGE

NORMAL HANDLING: (Always wear recommended personal protective equipment.)

Handle with care. Edges of material are very sharp.

### STORAGE RECOMMENDATIONS:

Store in a facility that will protect product from physical damage and/or contamination with foreign material. (Do not expose to moisture or any other substance.)

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **ENGINEERING CONTROLS:**

Use mechanical ventilation when cutting, grinding, sanding and/or welding product.

### PERSONAL PROTECTIVE EQUIPMENT

### SKIN PROTECTION:

Wear cut-resistant gloves.

#### **EYE PROTECTION:**

Wear safety glasses when grinding, sanding, cutting and/or welding product.

### RESPIRATORY PROTECTION:

If necessary to meet exposure limits listed in section 8, wear an air-purifying respirator during grinding, sanding, cutting and/or welding activities.



# Metglas® MBF-67 Nickel-Based Brazing Foil

### **ADDITIONAL RECOMMENDATIONS:**

A safety shower, eyewash or another source of running water should be available in areas where grinding, sanding, cutting and/or welding operations take place.

### **EXPOSURE GUIDELINES**

INGREDIENT NAME	ACGIH TLV	OSHA PEL	<b>OTHER LIMIT</b>
Cobalt (possible trace impurity)	$0.02 \text{ mg/m}^3 \text{ (TWA)}$	$0.1 \text{ mg/m}^3 \text{ (TWA)}$	***End of shift:
			15 <i>u</i> g/l – urine
			1 <i>u</i> g/l - blood
Nickel	1.5 mg/m³ (TWA)	1 mg/m³ (TWA)	None
	inhalable fraction		
Phosphorous	0.02 ppm (TWA)	$0.1 \text{ mg/m}^3 \text{ (TWA)}$	None
Chromium (trivalent)	0.5 mg/m3 (TWA)	1 mg/m3 (TWA)	None
		metal	
Iron	5 mg/m3 (TWA) as	10 mg/m3 (TWA) as	None
	iron oxide	iron oxide fume	
Molybdenum	10 mg/m3 (TWA)	15 mg/m3 (TWA)	None
Silicon	10 mg/m3 (TWA)	15 mg/m3 (TWA) as	None
		total dust.	
		5 mg/m3 (TWA) as	
		respirable dust.	
Boron (oxide)	10 mg/m3 (TWA)	15  mg/m 3  (TWA) as	None
		total dust.	

<sup>\*\*\* =</sup> Biological Exposure Index (ACGIH).

### OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

None

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** A shiny metallic ribbon.

PHYSICAL STATE: Solid

MOLECULAR WEIGHT: Metal alloy mixture CHEMICAL FORMULA: Metal alloy mixture

**ODOR:** None

SPECIFIC GRAVITY (water = 1.0): 7.4 – 8.2 SOLUBILITY IN WATER (weight %): None

**pH:** Not applicable

**BOILING POINT:** Not applicable

**MELTING POINT:** 1634 – 1940 °F (890 – 1060 °C)

**VAPOR PRESSURE:** Not applicable **VAPOR DENSITY (air = 1.0):** Not applicable

**EVAPORATION RATE:** Not applicable **COMPARED TO:** 

% VOLATILES: None FLASH POINT: None



# Metglas® MBF-67 Nickel-Based Brazing Foil

(Flash point method and additional flammability data are found in Section 5.)

### 10. STABILITY AND REACTIVITY

### NORMALLY STABLE? (CONDITIONS TO AVOID):

Normally stable.

### **INCOMPATIBILITIES:**

Product can be attacked by moisture and corrosive materials.

### HAZARDOUS DECOMPOSITION PRODUCTS:

Toxic vapors and metallic fumes may be released if melted in a fire (see section 3).

#### HAZARDOUS POLYMERIZATION:

Not applicable.

### 11. TOXICOLOGICAL INFORMATION

#### **IMMEDIATE (ACUTE) EFFECTS:**

Nickel: LD<sub>50</sub> (dermal, rabbit) >2 g/kg Nickel may cause dermal sensitization.

### **DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:**

Nickel: IARC lists cobalt as a class 2b possible carcinogen based on animal test data. Listed as a 'suspect carcinogen by NTP. Chronic inhalation may cause pneumoconiosis and kidney effects.

 $Phosphorous: \ Repeated \ inhalation \ of \ phosphorous \ may \ cause \ liver \ and \ kidney \ effects.$ 

### **OTHER DATA:**

None

### 12. ECOLOGICAL INFORMATION

Not anticipated to present an ecological hazard.

### 13. DISPOSAL CONSIDERATIONS

### **RCRA**

Is the unused product a RCRA hazardous waste if discarded? No If yes, the RCRA ID number is:

**OTHER DISPOSAL CONSIDERATIONS:** Observe all Federal, State, and Local Environmental regulations. Some local regulations may restrict disposal of metallic waste based on composition. Recycling of metallic products is recommended where recycling programs are available.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.



## Metglas® MBF-67 Nickel-Based Brazing Foil

### 14. TRANSPORT INFORMATION

US DOT PROPER SHIPPING NAME:
US DOT HAZARD CLASS:
Not regulated
Not regulated
Not regulated

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

### 15. REGULATORY INFORMATION

### TOXIC SUBSTANCES CONTROL ACT (TSCA)

**TSCA INVENTORY STATUS:** An article manufactured from ingredients listed on the TSCA Inventory.

OTHER TSCA ISSUES: None

### **SARA TITLE III/CERCLA**

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

INGREDIENT NAME	SARA/CERCLA RQ (lb)	SARA EHS TPQ (lb)
Nickel	100	None
Phosphorous	1	100
Chromium	5000	None

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: Immediate

### **SARA 313 TOXIC CHEMICALS:**

The following ingredients are SARA 313 "Toxic Chemicals". CAS numbers and weight percents are found in Section 2.

INGREDIENT NAME COMMENT

Cobalt (possible trace impurity)

Nickel

Phosphorous

None

None

### **STATE RIGHT-TO-KNOW**

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

INGREDIENT NAME WEIGHT % COMMENT

Cobalt (possible trace impurity) 0-1 Listed as California Proposition 65 carcinogen.



## Metglas® MBF-67 Nickel-Based Brazing Foil

Nickel 60-80 Listed as California Proposition 65 carcinogen.

### ADDITIONAL REGULATORY INFORMATION:

None**WHMIS CLASSIFICATION (CANADA):**D2B (sensitizer). Basis: Product as shipped. This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### FOREIGN INVENTORY STATUS:

Article: Ingredients are listed on Canadian DSL and European EINECS.

### 16. OTHER INFORMATION

**OTHER INFORMATION:** Contact Metglas®, Inc. if you have specific questions regarding the handling of or applications for this product.



## Metglas® MBF-67 Nickel-Based Brazing Foil

Date	Rev. Number	Revision Description
08/24/14	00	Initial release

Issue Date: 08/24/14	Rev. Date:	Confidential	Yes <b>☑</b>	No □	
HS&E Leader	Director, Quality Assurance				
J. Schwindel	J. Smith				