

# Metglas® MBF-1000 Series Brazing Foil

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** METGLAS® MBF-1000 Series Nickel-Based Brazing Foil

OTHER/GENERIC NAMES: MBF-1000 Series Brazing Foil; MBF-1000 Series Brazing Filler Metals

The MBF-1000 Series includes the following grades: 1001, 1002, 1004, 1005, 1006,

IN CASE OF EMERGENCY CALL:

1007, 1008, 1010, 1011, 1012, 1020, 1022

**PRODUCT USE:** Metal joining; Hard facing

**MANUFACTURER:** Metglas®, Inc.

440 Allied Dr.

Conway, SC - 29526

### FOR MORE INFORMATION CALL:

(Monday-Friday, 8:00am-5:00pm) (24 Hours/Day, 7 Days/Week)

1-800-581-7654 or Chemtrec 1-800-424-9300

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME		<b>CAS NUMBER</b>	WEIGHT %
Boron	(present in grades 1001, 1002, 1012 and 1022)	7440-42-8	0 - 5
Chromium	(present in grades 1001, 1002, and 1012)	7440-47-3	0 - 15
Cobalt	(present in grades 1011, 1020 and 1022)	7440-48-4	0 - 15
Iron	(present in grades 1001, 1002 and 1010)	7439-89-6	0 - 25
Palladium	(present in all grades)		25 - 90
Molybdenum (present in grades 1011 and 1022) 7439-98-7 0 -			0 - 8
Nickel	(present in all grades)	7440-02-0	5 - 60
Silicon	(present in all grades except 1001 and 1002)	7440-21-3	0 - 10

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of the MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

### 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: A shiny metallic foil. As shipped, the primary hazard is the sharp edges of the product. Some individuals may develop allergic skin reactions after repeated handling. If melted in a fire, toxic fumes may be released.

### POTENTIAL HEALTH HAZARDS

SKIN: Handling of sharp edges may cause cuts. Repeated contact may cause allergic skin reaction

resulting in irritation or dermatitis.

EYES: Not a normal route of entry. Solid particles generated by grinding and sanding may cause

irritation.



## Metglas® MBF-1000 Series Brazing Foil

**INHALATION:** Vapors and fumes resulting from the grinding, sanding, cutting and/or welding of this

material are harmful if inhaled. Symptoms may include irritation of throat and respiratory

tract. Exposures may result in "metal fume fever" which can produce flu-like symptoms.

**INGESTION:** Not a route of entry.

**DELAYED EFFECTS:** Repeated inhalation of vapors and fumes may result in toxic effects to the lungs.

Cobalt and cobalt foils and nickel and nickel compounds have caused cancer in laboratory animals and should be treated as 'possible' carcinogens. At present there is no reliable evidence that cobalt or nickel metal has caused cancer in humans.

Long term nickel exposure may affect kidney function.

Although hexavalent chrome is considered a potential carcinogen, the trivalent

(metallic) chrome in this product is not considered to be a carcinogen.

Ingredients found on one of the OSHA designated carcinogen lists are listed below.

INGREDIENT NAMENTP STATUS<br/>NoneIARC STATUS<br/>2b - possible<br/>carcinogenOSHA LIST<br/>NoneNickelSuspect<br/>carcinogen2b - possible<br/>carcinogenNone

### 4. FIRST AID MEASURES

**SKIN:** Wash hands with soap and water.

**EYES:** For irritation caused by particles of dust flush eyes with running water. Seek medical assistance if irritation

persists.

**INHALATION:** Remove to fresh air immediately. If breathing is difficult, get immediate medical assistance.

Oxygen may be given by a person trained and qualified to administer it.

**INGESTION:** Not a route of entry.

**ADVICE TO PHYSICIAN:** Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

### **FLAMMABLE PROPERTIES**

FLASH POINT: None

**FLASH POINT METHOD:** Not applicable

**AUTOIGNITION TEMPERATURE:** Not applicable

UPPER FLAME LIMIT (volume % in air):

LOWER FLAME LIMIT (volume % in air):

Not applicable
Not determined.

OSHA FLAMMABILITY CLASS: None



# Metglas® MBF-1000 Series Brazing Foil

### **EXTINGUISHING MEDIA:**

Use any standard agent for surrounding fire.

### **UNUSUAL FIRE AND EXPLOSION HAZARDS:**

None

### SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Toxic and irritating vapors may be released if the product melts or burns in a fire. Use self-contained respiratory protection.

### 6. ACCIDENTAL RELEASE MEASURES

#### IN CASE OF SPILL OR OTHER RELEASE:

Material is shipped as an article. Pick up and place into proper storage. Use caution in handling as edges are very sharp.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

### 7. HANDLING AND STORAGE

NORMAL HANDLING: (Always wear recommended personal protective equipment.)

Handle with care. Edges of material are very sharp.

#### STORAGE RECOMMENDATIONS:

Store in a facility that will protect product from physical damage and/or contamination with foreign material. (Do not exposure to moisture or any other substance.)

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### **ENGINEERING CONTROLS:**

Use mechanical ventilation when cutting, grinding, sanding and/or welding product.

### PERSONAL PROTECTIVE EQUIPMENT

### SKIN PROTECTION:

Wear cut-resistant gloves.

### **EYE PROTECTION:**

Wear safety glasses when grinding, sanding, cutting and/or welding product.

### **RESPIRATORY PROTECTION:**

If necessary to meet exposure limits listed in section 8, wear an air-purifying respirator during grinding, sanding, cutting and/or welding activities.

### **ADDITIONAL RECOMMENDATIONS:**

A safety shower, eyewash or another source of running water should be available in areas where grinding, sanding, cutting and/or welding operations take place.



# Metglas® MBF-1000 Series Brazing Foil

### **EXPOSURE GUIDELINES**

INGREDIENT NAME	ACGIH TLV	OSHA PEL	<b>OTHER LIMIT</b>
Chromium (trivalent)	$0.5 \text{ mg/m}^3 \text{ (TWA)}$	1 mg/m³ (TWA) metal	None
Cobalt	$0.02 \text{ mg/m}^3 \text{ (TWA)}$	$0.1 \text{ mg/m}^3 \text{ (TWA)}$	***End of shift:
			15 <i>u</i> g/l – urine
			1 <i>u</i> g/l - blood
Iron	5 mg/m <sup>3</sup> (TWA) as iron	10 mg/m <sup>3</sup> (TWA) as iron	None
	oxide	oxide fume	
Molybdenum	$10 \text{ mg/m}^3 \text{ (TWA)}$	15 mg/m³ (TWA)	None
Nickel	1.5 mg/m³ (TWA) inhalable	1 mg/m³ (TWA)	None
	fraction	<b>G</b>	
Silicon	$10 \text{ mg/m}^3 \text{ (TWA)}$	15 mg/m <sup>3</sup> (TWA) as total	None
	<b>3</b>	dust.	
		5 mg/m <sup>3</sup> (TWA) as	
		respirable dust.	

<sup>\* =</sup> Limit established by Honeywell International, Inc.

### OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

None

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** A shiny metallic ribbon.

PHYSICAL STATE: Solid

MOLECULAR WEIGHT: Metal alloy mixture CHEMICAL FORMULA: Metal alloy mixture

ODOR: None

SPECIFIC GRAVITY (water =  $1.0 \text{ g/cm}^3$ ): MBF-1001 8.80

MBF-1002 8.85

MBF-1004 not determined

MBF-1005 9.93 MBF-1006 9.60 MBF-1007 9.11 MBF-1008 11.04 MBF-1010 10.13 MBF-1012 8.82

MBF-1020 not determined

MBF-1022 8.88

**SOLUBILITY IN WATER (weight %):** None

**pH**: Not applicable

<sup>\*\* =</sup> Workplace Environmental Exposure Level (AIHA).

<sup>\*\*\* =</sup> Biological Exposure Index (ACGIH).



## Metglas® MBF-1000 Series Brazing Foil

**BOILING POINT:** Not applicable

 MELTING
 MBF-1001: 1733 – 1825°F (945 – 996°C)
 MBF-1008: 1422 – 1508°F (772 – 820°C)

 RANGE, T<sub>S</sub>
 MBF-1002: 1693 – 1814°F (923 – 990°C)
 MBF-1010: 1760 – 1868°F (960 – 1020°C)

,  $T_L$  MBF-1004: not determined MBF-1011: 1557 – 1643°F (847 – 895°C)

MBF-1005: 1490 – 1564°F (810 – 851°C) MBF-1012: 1508-1760°F (820-960°C MBF-1006: not determined MBF-1020: 1508 – 1598°F (820 – 870°C) MBF-1007: 1508-1598°F (820-870°C) MBF-1022: 1539 – 1605°F (837 – 874°C)

**VAPOR PRESSURE:** Not applicable **VAPOR DENSITY (air** Not applicable

= 1.0):

**EVAPORATION** Not applicable **COMPARED TO**:

RATE:

% VOLATILES: None FLASH POINT: None

(Flash point method and additional flammability data are found in Section 5.)

### 10. STABILITY AND REACTIVITY

### NORMALLY STABLE? (CONDITIONS TO AVOID):

Normally stable.

#### **INCOMPATIBILITIES:**

Product can be attacked by moisture and corrosive materials.

#### HAZARDOUS DECOMPOSITION PRODUCTS:

Toxic vapors and metallic fumes may be released if melted in a fire (see section 3).

### **HAZARDOUS POLYMERIZATION:**

Not applicable.

### 11. TOXICOLOGICAL INFORMATION

### **IMMEDIATE (ACUTE) EFFECTS:**

Iron: LD<sub>50</sub> (oral, rat) 30 g/kg

Nickel: LD<sub>50</sub> (dermal, rabbit) >2 g/kg Nickel may cause dermal sensitization.

Silicon: LD<sub>50</sub> (oral, rat) 3.16 g/kg

### **DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:**

Chromium: Repeated inhalation of trivalent chrome may cause respiratory tract inflammation and lung effects.

Cobalt: IARC lists cobalt compounds as class 2b possible carcinogens based on animal test data.

Nickel: IARC lists nickel as a class 2b possible carcinogen based on animal test data. Listed as a 'suspect carcinogen by NTP. Chronic inhalation may cause pneumoconiosis and kidney effects.

Silicon: Repeated inhalation of silicon may cause lung effects.

**OTHER DÂTA:** 

None

### 12. ECOLOGICAL INFORMATION

Not anticipated to present an ecological hazard.



# Metglas® MBF-1000 Series Brazing Foil

### 13. DISPOSAL CONSIDERATIONS

### **RCRA**

Is the unused product a RCRA hazardous waste if discarded? No If yes, the RCRA ID number is:

**OTHER DISPOSAL CONSIDERATIONS:** Observe all Federal, State, and Local Environmental regulations. Some local regulations may restrict disposal of metallic waste based on composition. Recycling of metallic products is recommended where recycling programs are available.

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

### 14. TRANSPORT INFORMATION

US DOT PROPER SHIPPING NAME:
US DOT HAZARD CLASS:
Not regulated
Not regulated
Not regulated

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

### 15. REGULATORY INFORMATION

### TOXIC SUBSTANCES CONTROL ACT (TSCA)

**TSCA INVENTORY STATUS:** An article manufactured from ingredients listed on the TSCA Inventory.

OTHER TSCA ISSUES: None

### SARA TITLE III/CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

INGREDIENT NAMESARA/CERCLA RQ (lb)SARA EHS TPQ (lb)Chromium5000NoneNickel100None

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: Immediate

**SARA 313 TOXIC CHEMICALS:** 



# Metglas® MBF-1000 Series Brazing Foil

The following ingredients are SARA 313 "Toxic Chemicals". CAS numbers and weight percents are found in Section 2.

<u>INGREDIE</u>	<b>COMMENT</b>	
Chromium	(Present in grades 1001, 1002, and 1012 only)	None
Cobalt	(Present in grades 1011, 1020 and 1022 only)	None
Nickel	(Present in all Series 1000 grades)	None

### **STATE RIGHT-TO-KNOW**

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

INGREDIENT NAME	<b>WEIGHT</b> %	<u>COMMENT</u>
Cobalt	15 max	Listed as California Proposition 65 carcinogen.
		(Present in grades 1011, 1020 and 1020 only)
Nickel	5 - 60	Listed as California Proposition 65 carcinogen
		(Present in all Series 1000 grades)

### ADDITIONAL REGULATORY INFORMATION:

None

### WHMIS CLASSIFICATION (CANADA):

D2B (sensitizer). Basis: Product as shipped.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

### FOREIGN INVENTORY STATUS:

Article: Ingredients are listed on Canadian DSL and European EINECS.

### 16. OTHER INFORMATION

OTHER INFORMATION: Contact Metglas®, Inc. if you have specific questions regarding the handling of or

applications for this product.



# Metglas® MBF-1000 Series Brazing Foil

Date	Rev. Number	Revision Description
October 2003	00	Initial release
02/06/13	01	Content review per J. Schwindel (system revised to maintain all Material Safety Data Sheets within ISODOC system and require minimum, a three year content review)

Issue Date: October 2003	Rev. Date: 02/06/13	Confidential	Yes <b>☑</b>	No □	
HS&E Leader Q	uality Manager				
J. Schwindel J.	Smith				