SAFETY DATA SHEET



MBF 15, 20,30, 50, 51, 53, 80, 23

Section 1. Identification

GHS product identifier : MBF 15, 20,30, 50, 51, 53, 80, 23

Product code : Not available.

Other means of identification

: Amorphous Braze Foil

Product type : Massive metal.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Brazing.

Area of application : Industrial applications.

Supplier's details : Metglas, Inc.

> 440 Allied Drive, Conway, SC 29526 United States

Telephone: 843-349-6800

www.metglas.com

e-mail address of person

responsible for this SDS

: john.schwindel@metglas.com and william.coughlan@metglas.com

Emergency telephone number (with hours of

operation)

: Manufacturer: 800-581-7654 (24/7) CHEMTREC: 800-424-9300 (24/7)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : H317 SKIN SENSITIZATION - Category 1 H351 CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2 H361

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) -H372

Category 1

GHS label elements

Hazard pictograms





Signal word Danger

Hazard statements : H317 - May cause an allergic skin reaction.

H351 - Suspected of causing cancer.

H361 - Suspected of damaging fertility or the unborn child.

H372 - Causes damage to organs through prolonged or repeated exposure. (central

nervous system (CNS), lungs, respiratory tract)

Date of issue/Date of revision : 07/17/2020 Date of previous issue : No previous validation Version: 1 1/13

Section 2. Hazards identification

Precautionary statements

Prevention : P201 - Obtain special instructions before use.

P280 - Wear protective gloves. Wear protective clothing. Wear eye or face protection.

P260 - Do not breathe dust.

P270 - Do not eat, drink or smoke when using this product.

: P308 + P313 - IF exposed or concerned: Get medical advice or attention. Response

P363 - Wash contaminated clothing before reuse.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

: Not applicable. **Storage**

: P501 - Dispose of contents and container in accordance with all local, regional, national **Disposal**

and international regulations.

Hazards not otherwise

classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of

identification

: Amorphous Braze Foil

Ingredient name	Other names	%	CAS number
Nickel	-	0 - 100	7440-02-0
iron	-	0 - 65	7439-89-6
Chromium	-	0 - 20	7440-47-3
silicon	-	0 - 8	7440-21-3
molybdenum	-	0 - 6	7439-98-7
boron	-	0 - 5	7440-42-8
manganese	-	0 - 2	7439-96-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Get medical attention.

Inhalation : Not applicable.

Skin contact : Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water

> before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure.

Cuts should be treated promptly and covered.

Ingestion : Not applicable.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Not applicable. Inhalation : Not applicable.

Skin contact : May cause an allergic skin reaction.

Ingestion : Not applicable.

Date of issue/Date of revision : 07/17/2020 Date of previous issue Version: 1 : No previous validation 2/13

Section 4. First aid measures

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

: Adverse symptoms may include the following: Skin contact

> irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

: Do not use water jet.

Specific hazards arising from the chemical

Hazardous thermal

decomposition products

: No specific fire or explosion hazard.

: Decomposition products may include the following materials:

metal oxide/oxides Vapor (Toxic)

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : No special protection is required.

Date of issue/Date of revision : 07/17/2020 Date of previous issue Version: 1 3/13 : No previous validation

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions: No specific hazard.

Methods and materials for containment and cleaning up

Small spill : Restack safely. Take care with items that are sharp or heavy.

Large spill : Restack safely. Take care with items that are sharp or heavy. Note: see Section 1 for

emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Take care with items that are sharp or heavy.

Advice on general occupational hygiene

: Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store locked up. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Nickel	ACGIH TLV (United States, 3/2019). TWA: 1.5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 0.015 mg/m³, (as Ni) 10 hours. OSHA PEL (United States, 5/2018). TWA: 1 mg/m³, (as Ni) 8 hours.
iron Chromium	None. ACGIH TLV (United States, 3/2019). TWA: 0.5 mg/m³, (measured as Cr) 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 0.5 mg/m³ 8 hours. OSHA PEL (United States, 5/2018). TWA: 1 mg/m³, (as Cr) 8 hours.

Date of issue/Date of revision : 07/17/2020 Date of previous issue : No previous validation Version : 1 4/13

Section 8. Exposure controls/personal protection

<u> </u>	-
silicon	NIOSH REL (United States, 10/2016).
	TWA: 5 mg/m³ 10 hours. Form: Respirable fraction
	TWA: 10 mg/m³ 10 hours. Form: Total
	OSHA PEL (United States, 5/2018).
	TWA: 5 mg/m³ 8 hours. Form: Respirable fraction
	TWA: 15 mg/m³ 8 hours. Form: Total dust
molybdenum	ACGIH TLV (United States, 3/2019).
	TWA: 10 mg/m³, (as Mo) 8 hours. Form: Inhalable
	fraction
	TWA: 3 mg/m³, (as Mo) 8 hours. Form: Respirable
	fraction
boron	None.
manganese	NIOSH REL (United States, 10/2016).
	TWA: 1 mg/m³, (as Mn) 10 hours. Form: Fume
	STEL: 3 mg/m³, (as Mn) 15 minutes. Form: Fume
	OSHA PEL (United States, 5/2018).
	CEIL: 5 mg/m³, (as Mn) Form: Fume
	ACGIH TLV (United States, 3/2019).
	TWA: 0.1 mg/m³, (as Mn) 8 hours. Form: Inhalable
	fraction
	TWA: 0.02 mg/m³, (as Mn) 8 hours. Form: Respirable
	fraction

Appropriate engineering controls

: No special ventilation requirements. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Not applicable.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Wash thoroughly after handling.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection Body protection

- : Use strong, cut-resistant gloves suitable for handling metals.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Not applicable.

Date of issue/Date of revision : 07/17/2020 Date of previous issue : No previous validation Version : 1 5/13

Section 9. Physical and chemical properties

Appearance

Physical state : Solid. [foil]
Color : Metallic-gray.
Odor : Odorless.
Odor threshold : Not available.
pH : Not applicable.

Melting point : 965 to 1195°C (1769 to 2183°F)

Boiling point : Not available.
Flash point : Not applicable.
Evaporation rate : Not applicable.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.

Relative density : 7.7 to 8.1 [Water = 1]

Density : Not available.

Solubility : Insoluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

SADT : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid : No specific data.

Incompatible materials : Reactive or incompatible with the following materials: moisture.

Corrosive material

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 07/17/2020 Date of previous issue : No previous validation Version : 1 6/13

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
iron	LD50 Oral	Rat	750 mg/kg	-
silicon	LD50 Oral	Rat	3160 mg/kg	-
molybdenum	LC50 Inhalation Dusts and mists	Rat	>5.84 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
boron	LC50 Inhalation Dusts and mists	Rat - Male,	>5.08 mg/l	4 hours
		Female		
	LD50 Oral	Rat	650 mg/kg	-
manganese	LC50 Inhalation Dusts and mists	Rat	5.14 mg/l	4 hours
_	LD50 Oral	Rat	9 g/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
silicon	Eyes - Mild irritant	Rabbit	-	3 mg	-
manganese	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
	Skin - Mild irritant	Rabbit	-	mg 24 hours 500 mg	-

Sensitization

Not available.

Mutagenicity

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Nickel	-	1	Reasonably anticipated to be a human carcinogen.
Chromium	-	3	-

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
molybdenum	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Nickel manganese	Category 1 Category 2	inhalation -	respiratory tract central nervous system (CNS), lungs

Date of issue/Date of revision : 07/17/2020 Date of previous issue : No previous validation Version : 1 7/13

Section 11. Toxicological information

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : Not applicable. Inhalation : Not applicable.

Skin contact : May cause an allergic skin reaction.

: Not applicable. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

: No specific data. **Eye contact**

Inhalation : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

> irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

effects

Potential delayed effects : Not available.

Potential chronic health effects

General : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a

severe allergic reaction may occur when subsequently exposed to very low levels.

Suspected of causing cancer. Risk of cancer depends on duration and level of Carcinogenicity

exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity

Numerical measures of toxicity

Acute toxicity estimates

Date of issue/Date of revision : 07/17/2020 Date of previous issue Version: 1 8/13 : No previous validation

Section 11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
MBF 15, 20,30, 50, 51, 53, 80, 23	N/A	2500	N/A	N/A	N/A
iron	750	N/A	N/A	N/A	N/A
silicon	3160	N/A	N/A	N/A	N/A
molybdenum	N/A	2500	N/A	N/A	N/A
boron	650	N/A	N/A	N/A	N/A
manganese	9000	N/A	N/A	N/A	5.14

Other information

: Adverse symptoms may include the following: Metal fume fever if exposed to high concentration of fumes.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Nickel	Acute EC50 2 ppm Marine water	Algae - Macrocystis pyrifera - Young	4 days
	Acute EC50 450 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute EC50 1000 µg/l Marine water	Daphnia - Daphnia magna	48 hours
	Acute IC50 0.31 mg/l Marine water	Crustaceans - Americamysis bahia - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 47.5 ng/L Fresh water	Fish - Heteropneustes fossilis	96 hours
	Chronic NOEC 100 mg/l Marine water	Algae - Glenodinium halli	72 hours
	Chronic NOEC 3.5 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
iron	Acute EC50 3700 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 33000 to 100000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 6.48 μg/l Marine water	Fish - Periophthalmus waltoni - Adult	96 hours
	Chronic NOEC 100 mg/l Marine water	Algae - Glenodinium halli	72 hours
Chromium	Acute EC50 0.2 ppm Marine water	Algae - Bacillariophyta	72 hours
	Acute EC50 5 ppm Marine water	Algae - Macrocystis pyrifera - Young	4 days
	Acute EC50 35000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 45 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 22 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 13.9 ppm Fresh water	Fish - Anguilla rostrata	96 hours
	Chronic NOEC 50 mg/l Marine water	Algae - Glenodinium halli	72 hours
	Chronic NOEC 0.19 µg/l Fresh water	Fish - Cyprinus carpio	4 weeks
molybdenum	Acute LC50 >200000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
•	Acute LC50 800 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 500 mg/l Marine water	Algae - Glenodinium halli	72 hours
manganese	Acute EC50 31000 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
-	Acute LC50 29000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 28 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 1.7 mg/l Fresh water	Daphnia - Water Flea- Ceriodaphnia dubia	8 days

Conclusion/Summary

: Not available.

Date of issue/Date of revision: 07/17/2020Date of previous issue: No previous validationVersion: 1

Section 12. Ecological information

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
silicon	57 to 77	-	high

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Additional information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

Date of issue/Date of revision : 07/17/2020 Date of previous issue Version: 1 10/13 : No previous validation

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are active or exempted.

Clean Water Act (CWA) 307: Nickel; Chromium

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : SKIN SENSITIZATION - Category 1

CARCINOGENICITY - Category 2

TOXIC TO REPRODUCTION - Category 2

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Composition/information on ingredients

Name	%	Classification
Nickel	0 - 100	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2
		SPECIFIC TARGET ORGAN TOXICITY (REPEATED
		EXPOSURE) - Category 1
iron	0 - 65	COMBUSTIBLE DUŠTŠ
		ACUTE TOXICITY (oral) - Category 4
silicon	0 - 8	FLAMMABLE SOLIDS - Category 2
		EYE IRRITATION - Category 2B
molybdenum	0 - 6	EYE IRRITATION - Category 2B
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
		(Respiratory tract irritation) - Category 3
boron	0 - 5	ACUTE TOXICITY (oral) - Category 4
manganese	0 - 2	FLAMMABLE SOLIDS - Category 2
		EYE IRRITATION - Category 2B
		TOXIC TO REPRODUCTION - Category 2
		SPECIFIC TARGET ORGAN TOXICITY (REPEATED
		EXPOSURE) - Category 2

SARA 313

Date of issue/Date of revision: 07/17/2020Date of previous issue: No previous validationVersion: 1

Section 15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	Nickel	7440-02-0	0 - 100
	Chromium	7440-47-3	0 - 20
	manganese	7439-96-5	0 - 2
Supplier notification	Nickel	7440-02-0	0 - 100
	Chromium	7440-47-3	0 - 20
	manganese	7439-96-5	0 - 2

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: NICKEL; NICKEL CATALYST; CHROMIUM;

SILICON DUST; MOLYBDENUM; MANGANESE

New York : The following components are listed: Nickel; Chromium

New Jersey : The following components are listed: NICKEL; CHROMIUM; SILICON; MOLYBDENUM;

BORON: MANGANESE

Pennsylvania The following components are listed: NICKEL CATALYST; CHROMIUM COMPOUNDS;

SILICON; MOLYBDENUM; MANGANESE COMPOUNDS

California Prop. 65

MARNING: This product can expose you to Nickel, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Nickel	-	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)


Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Date of issue/Date of revision : 07/17/2020 Date of previous issue Version: 1 12/13 : No previous validation

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method

History

Date of issue/Date of

revision

Version

Date of previous issue

- 4

Prepared by

: Sphera Solutions

: No previous validation

Key to abbreviations

: ATE = Acute Toxicity Estimate

AMP = Acceptable maximum peak above the acceptable ceiling concentration for an

8-hr shift

: 07/17/2020

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available UN = United Nations

References

: HCS (U.S.A.)- Hazard Communication Standard

International transport regulations

Indicates information that has changed from previously issued version.

Notice to reader

The Metglas Braze Foil is intended to be used as a braze filler metal in a vacuum or inert atmosphere braze furnace. Since the actual use by others is beyond our control, it is the user's responsibility to determine the suitability of the product for its use and to adopt such safety precautions as may be necessary. Since the conditions of use are not under our control, Metglas disclaims all liability with respect to the use of any material supplied by Metglas.

Date of issue/Date of revision : 07/17/2020 Date of previous issue : No previous validation Version : 1 13/13